

美国 Cannon 标准油

类 别	规格型号	货 号	包 装	适用方法
通用粘度 标油	N.4	9727-C10	500mL/瓶	ASTM D445/446 ISO 3104/3105
	N.8	9727-C15	500mL/瓶	
	N1.0	9727-C20	500mL/瓶	
	N2	9727-C22	500mL/瓶	
	S3	9727-C25	500mL/瓶	
	N4	9727-C27	500mL/瓶	
	S6	9727-C30	500mL/瓶	
	N7.5	9727-C31	500mL/瓶	
	N10	9727-C32	500mL/瓶	
	N14	9727-C34	500mL/瓶	
	S20	9727-C35	500mL/瓶	
	N26	9727-C36	500mL/瓶	
	N35	9727-C37	500mL/瓶	
	N44	9727-C38	500mL/瓶	
	S60	9727-C40	500mL/瓶	
	N75	9727-C41	500mL/瓶	
	N100	9727-C42	500mL/瓶	
	N140	9727-C43	500mL/瓶	
	S200	9727-C45	500mL/瓶	
	N250	9727-C46	500mL/瓶	
	N350	9727-C47	500mL/瓶	
	N415	9727-C48	500mL/瓶	
	S600	9727-C50	500mL/瓶	
	N750	9727-C51	500mL/瓶	
	N1000	9727-C52	500mL/瓶	
	N1400	9727-C53	500mL/瓶	
	S2000	9727-C55	500mL/瓶	
	N2500	9727-C56	500mL/瓶	
	N400	9727-C57	500mL/瓶	
	N5100	9727-C58	500mL/瓶	
	S8000	9727-C60	500mL/瓶	
	N10200	9727-C61	500mL/瓶	
	N15000	9727-C62	500mL/瓶	
	N18000	9727-C63	500mL/瓶	
	S30000	9727-C65	500mL/瓶	

类 别	规格型号	货 号	包 装	适用方法
CCS 粘度标油	CL080	9727-N02	500mL/瓶	ASTM D5293
	CL090	9727-N04	500mL/瓶	
	CL100	9727-N06	500mL/瓶	
	CL110	9727-N07	500mL/瓶	
	CL120	9727-N08	500mL/瓶	
	CL130	9727-N09	500mL/瓶	
	CL140	9727-N10	500mL/瓶	
	CL150	9727-N11	500mL/瓶	
	CL160	9727-N12	500mL/瓶	
	CL170	9727-N13	500mL/瓶	
	CL190	9727-N14	500mL/瓶	
	CL200	9727-N16	500mL/瓶	
	CL220	9727-N18	500mL/瓶	
	CL240	9727-N20	500mL/瓶	
	CL250	9727-N22	500mL/瓶	
	CL260	9727-N24	500mL/瓶	
	CL280	9727-N26	500mL/瓶	
	CL300	9727-N28	500mL/瓶	
	CL320	9727-N30	500mL/瓶	
	CL340	9727-N31	500mL/瓶	
	CL380	9727-N32	500mL/瓶	
	CL420	9727-N33	500mL/瓶	
	CL480	9727-N34	500mL/瓶	
	CL530	9727-N35	500mL/瓶	
	CL600	9727-N36	500mL/瓶	
	CL680	9727-N37	500mL/瓶	
	CL740	9727-N38	500mL/瓶	
	8CL	9727-N42	500mL/瓶	
	14CL	9727-N43	500mL/瓶	
	CL-NNR	9727-N45	500mL/瓶	
硅 油	RT5	9727-Z10	500mL/瓶	
	RT10	9727-Z14	500mL/瓶	
	RT50	9727-Z18	500mL/瓶	
	RT100	9727-Z22	500mL/瓶	
	RT500	9727-Z26	500mL/瓶	
	RT1000	9727-Z30	500mL/瓶	
	RT5000	9727-Z34	500mL/瓶	
	RT12500	9727-Z38	500mL/瓶	
	RT30000	9727-Z42	500mL/瓶	
	RT60000	9727-Z46	500mL/瓶	
	RT100000	9727-Z50	500mL/瓶	

类 别	规格型号	货 号	包 装	适用方法
高温粘度 标油	N600	9727-E10	500mL/瓶	ASTM D2170/2171
	N1000	9727-C52	500mL/瓶	
	N2000	9727-E15	500mL/瓶	
	N4000	9727-C57	500mL/瓶	
	N8000	9727-E20	500mL/瓶	
	M15000	9727-C62	500mL/瓶	
	N30000	9727-E25	500mL/瓶	
	N62000	9727-E27	500mL/瓶	
	N150000	9727-E29	500mL/瓶	
	N190000	9727-E30	500mL/瓶	
	N450000	9727-E35	500mL/瓶	
	N2700000	9727-E40	500mL/瓶	
	N2700000SP	9727-E42	500mL/瓶	
低温粘度 标油	N27B	9727-G10	500mL/瓶	ASTM D2983
	N27C	9727-G12	500mL/瓶	
	N115B	9727-G15	500mL/瓶	
	N60B	9727-G25	500mL/瓶	
	N120B	9727-G30	500mL/瓶	
	N480B	9727-G35	500mL/瓶	
	N1400B	9727-G40	500mL/瓶	
	N2B	9727-G45	500mL/瓶	
	N74B	9727-G50	500mL/瓶	
	N38B	9727-G55	500mL/瓶	
	N25B	9727-G60	500mL/瓶	
	N14B	9727-G65	500mL/瓶	
MRV 标油	N105B	9727-T10	500mL/瓶	ASTM D3829 ASTM D4684
	YS-30	9727-T20	500mL/瓶	
	YS-35	9727-T25	500mL/瓶	

类 别	规格型号	货 号	包 装	适用方法
闪点 标油	FPRM10	9727-A10	200mL/瓶	ASTM D56 (50℃) , ASTM D93 (55℃)
	FPRM11	9727-A15	200mL/瓶	ASTM D56 (66℃) , ASTM D93 (72℃)
	FPRM14	9727-A20	200mL/瓶	ASTM D92 (116℃) , ASTM D93 (113℃)
	FPRM16	9727-A25	200mL/瓶	ASTM D92 (137℃) , ASTM D93 (132℃)
	FPRM2D	9727-A30	200mL/瓶	ASTM D92 (163℃) , ASTM D93 (155℃)
	FPRM4D	9727-A35	200mL/瓶	ASTM D92 (224℃) , ASTM D93 (218℃)
	FPRM9D	9727-A40	200mL/瓶	ASTM D92 (273.8℃) , ASTM D93 (224.1℃)

类 别	规格型号	货 号	包 装	适用方法
高温高剪 粘度标油	HT22	9727-U45	500mL/瓶	ASTM D5481
	HT39	9727-U50	500mL/瓶	
	HT75	9727-U55	500mL/瓶	
	HT150	9727-U60	500mL/瓶	
	HT240	9727-U65	500mL/瓶	
	HT390	9727-U70	500mL/瓶	
	HTNN-1	9727-U92	500mL/瓶	
	HTNN-2	9727-U94	500mL/瓶	
	RL 102	9727-R10.032	500mL/瓶	
	RL 103	9727-R15.032	500mL/瓶	
	RL 104	9727-R20.032	500mL/瓶	
	RL 105	9727-R25.032	500mL/瓶	
	RL 106	9727-R30.032	500mL/瓶	
	RL 107	9727-R35.032	500mL/瓶	